



US007942192B2

(12) **United States Patent**
Yamamoto et al.

(10) **Patent No.:** **US 7,942,192 B2**

(45) **Date of Patent:** **May 17, 2011**

(54) **VEHICLE AIR CONDITIONER**

(75) Inventors: **Takehiro Yamamoto**, Hiroshima (JP);
Tadashi Okamoto, Hiroshima (JP);
Hideaki Yasuda, Hiroshima (JP);
Hiroshi Mayumi, Hiroshima (JP);
Morihito Tsukuda, Hiroshima (JP);
Kenichiro Higashi, Hiroshima (JP);
Keiji Koga, Hiroshima (JP); **Yoshinori**
Aono, Hiroshima (JP)

(73) Assignee: **Japan Climate Systems Corporation**
(JP)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/448,845**

(22) Filed: **Jun. 8, 2006**

(65) **Prior Publication Data**

US 2006/0219384 A1 Oct. 5, 2006

Related U.S. Application Data

(62) Division of application No. 10/250,920, filed as
application No. PCT/JP02/08847 on Aug. 30, 2002,
now Pat. No. 7,100,675.

(30) **Foreign Application Priority Data**

Sep. 3, 2001 (JP) 2001-265798
Sep. 3, 2001 (JP) 2001-265815
Sep. 3, 2001 (JP) 2001-265833

(51) **Int. Cl.**
B60H 1/00 (2006.01)

(52) **U.S. Cl.** **165/42; 62/244; 62/291**

(58) **Field of Classification Search** 165/41,
165/42, 43, 44, 202, 203, 204, 248, 287,
165/247; 62/244, 159, 245, 291; 237/2 A
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,755,107 A	5/1998	Shirota et al.	
5,860,593 A	1/1999	Heinle et al.	
5,987,905 A *	11/1999	Nonoyama et al.	62/244
6,029,739 A *	2/2000	Izawa et al.	165/42
6,044,656 A *	4/2000	Shirota et al.	62/244
6,110,035 A	8/2000	Uemura et al.	
6,125,646 A *	10/2000	Ebner	62/298
7,036,576 B2 *	5/2006	Okamoto et al.	165/42

FOREIGN PATENT DOCUMENTS

DE	19534738	3/1996
EP	0578582	1/1994
EP	0930186 A1	7/1999
EP	1078786 A2	2/2001
GB	2328012 A	2/1999
JP	49-132536 A	12/1974

(Continued)

OTHER PUBLICATIONS

Apr. 20, 2004 Office Action for JP Application No. 2001-265833.

(Continued)


Primary Examiner — Ljiljana (Lil) V Ciric

(74) *Attorney, Agent, or Firm* — Studebaker & Brackett PC;
Donald R. Studebaker

(57) **ABSTRACT**

In an air conditioner constructed to pass an air introduced into
an air conditioning unit through an evaporator and a heater
core both arranged in the unit, cooler pipes for the evaporator
and heater pipes for the heater core are arranged to extend
from the same side wall of the air conditioning unit.

9 Claims, 24 Drawing Sheets



US 7,942,192 B2

Page 2

FOREIGN PATENT DOCUMENTS

JP	59149818	8/1984
JP	59195412	11/1984
JP	62-192908 A	12/1987
JP	01269609	10/1989
JP	8-104129	4/1996
JP	09-123748	5/1997
JP	11-091338	4/1999
JP	11-263118	9/1999
JP	11-348527	12/1999
JP	2000-318430	11/2000
JP	2001-039144	2/2001

JP	2001-206051	7/2001
JP	2001-213142	8/2001
WO	0153122	7/2001

OTHER PUBLICATIONS

Andreas Gumbel, Partial European Search Report, EP07019067, Feb. 16, 2009.

Extended European Search Report dated Oct. 19, 2009; Application No./Patent No. 07019067.3-2423/1864837.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23






FIG. 24

(a)



(b)



VEHICLE AIR CONDITIONER

TECHNICAL FIELD

This invention generally relates to vehicle air conditioners, and particularly relates to the technical field for layout structures of heater pipes and cooler pipes which are disposed around an air conditioning unit.

BACKGROUND ART

There has been conventionally known an exemplary vehicle air conditioner including an air conditioning unit with a cooling heat exchanger and a heating heat exchanger and an air blowing unit for blowing air into the air conditioning unit, for example, as disclosed in Japanese Unexamined Patent Publication No. 9-123748. The air conditioning and air blowing units are disposed inside of an instrument panel so as to be located substantially in the widthwise middle of a car and toward the front-passenger's seat, respectively.

The air conditioning unit is provided at its bottom end side with an air inlet leading from the air blowing unit. An air introduced into the air conditioning unit through the inlet passes through the cooling and heating heat exchangers, which are located above the inlet and substantially horizontally arranged one above the other, and is guided into the passenger's room through a duct extending from above the heat exchangers. With this air conditioning unit, juxtaposition of two heat exchangers one above the other allows the air conditioning unit to be downsized and thereby to be reduced in its installation space.

In the above prior art air conditioner disclosed, cooler pipes for an evaporator as a cooling heat exchanger and heater pipes for a heater core as a heating heat exchanger are arranged at the side wall of the air conditioning unit toward the air blowing unit or at the opposite side wall thereof. A drain port is provided at a suitable position of a bottom wall part of the air conditioning unit to drain off water downward.

Also, in the prior art air conditioner, the cooler pipes and heater pipes are attached to a dash panel disposed at the front of the air conditioning unit, but there is no clear description about specific positions at which the pipes are actually attached to the dash panel.

Furthermore, in the above prior art, the bottom end of the vertically elongated air conditioning unit is located in the vicinity of the floor of the vehicle body, whereas the air blowing unit has to be disposed sufficiently away from the floor in order to obtain legroom at the front of the front-passenger's seat. This invites a large level difference between the outlet of the air blowing unit and the inlet of the air conditioning unit. In this case, in order to smoothly send the air from the blowing unit to the air conditioning unit, it is necessary to space both the units away from each other by a predetermined distance or more in the car widthwise direction.

DISCLOSURE OF INVENTION

The present invention has been made in view of the foregoing points. The present invention is directed to a vehicle air conditioner in which a cooling heat exchanger and a heating heat exchanger are disposed in an air conditioning unit and air is sent from an air blowing unit disposed at the front-passenger's side of the air conditioning unit to the bottom end of the air conditioning unit, and has an object of facilitating the

attachment of heater pipes and cooler pipes to a vehicle body (dash panel) and further reducing the size of the air conditioner.

Solutions of the present invention taken to attain the above object are characterized in that the heater pipes and cooler pipes are arranged at the same side of the air conditioning unit so as to be located close to each other, and, in particular, both pipes are extended out of a side wall of the air conditioning unit located toward the air blowing unit, brought into proximity to each other and then bent substantially at a right angle toward the dash panel.

More specifically, a first solution of the invention is directed to a vehicle air conditioner comprising: an air conditioning unit disposed substantially in the middle of the inside of an instrument panel in a widthwise direction of a vehicle; an air blowing unit disposed to a front-passenger's side of the air conditioning unit; an intermediate duct for ducting an air from the air blowing unit to the air conditioning unit; and a cooling heat exchanger and a heating heat exchanger disposed in the air conditioning unit, in which the air introduced from the intermediate duct into the air conditioning unit is allowed to pass through the cooling and heating heat exchangers disposed in the air conditioning unit to produce a conditioned air. Further, cooler pipes connected to the cooling heat exchanger and heater pipes connected to the heating heat exchanger are arranged to extend from the same side of the air conditioning unit in the widthwise direction of the vehicle.

With this configuration, the heater pipes and the cooler pipes are arranged at the same side of the air conditioning unit. Therefore, in attaching the air conditioning unit to the dash panel, alignment can be made easily and workability of attachment can be increased. Since the heater pipes and the cooler pipes are arranged in proximity to each other, this enables downsizing of the air conditioning unit.

A second solution of the invention is directed to a vehicle air conditioner comprising: an air conditioning unit disposed substantially in the middle of the inside of an instrument panel in a widthwise direction of a vehicle; an air blowing unit disposed to a front-passenger's side of the air conditioning unit; and an intermediate duct for ducting an air from the air blowing unit to the air conditioning unit; in which the air introduced from the intermediate duct into the air conditioning unit is allowed to pass through a cooling heat exchanger and a heating heat exchanger juxtaposed one above the other in the air conditioning unit to produce a conditioned air. In this air conditioner, cooler pipes connected to the cooling heat exchanger and heater pipes connected to the heating heat exchanger are arranged to extend from the side of the air conditioning unit in the widthwise direction of the vehicle.

With this configuration, like the solution according to Claim 1, workability of air conditioning unit attachment can be increased and the air conditioning unit can be made compact.

With a third solution of the invention, in the vehicle air conditioner of, the cooler pipes and heater pipes are extended from the same side wall of the air conditioning unit, bent substantially at a right angle, brought into proximity to each other and then extended toward the front of the vehicle. Therefore, a space located laterally from the side wall of the air conditioning unit can be effectively used, and the air conditioning unit can be arranged in proximity to the dash panel, which increases the utilization area of the passenger's room.

With a fourth solution of the invention, in the vehicle air conditioner, the cooler pipes and heater pipes are extended from a side wall of the air conditioning unit, bent substantially

at a right angle, brought into proximity to each other and then extended toward the front of the vehicle, and all the cooler and heater pipes pass through through holes in proximity to each other in a dash panel disposed at the front of the air conditioning unit to locate distal ends thereof in an engine room beyond the dash panel. This facilitates the attachment of the air conditioning unit to the dash panel and improves sealing properties between all the pipes and the dash panel.

With a fifth solution of the invention, in the vehicle air conditioner, the side wall of the air conditioning unit from which the cooler pipes and heater pipes are extended is at the side of the air conditioning unit located toward the air blowing unit, and the cooler pipes and heater pipes are extended from between the air conditioning unit and the air blowing unit toward the front of the vehicle. Therefore, the space between the air conditioning unit and the air blowing unit can be effectively used. Furthermore, a space located laterally from the air conditioning unit and opposite to the air blowing unit, i.e., a space on the driver's side of the air conditioning unit, can be obtained amply. Alternatively, a large-sized temperature-control duct can be provided on the driver's side wall of the air conditioning unit to effectively carry out the temperature control on the passenger's room.

With a sixth solution of the invention, in the vehicle air conditioner, a bracket for supporting the cooler pipes and heater pipes is formed integrally with the air conditioning unit, and the bracket supports portions of the cooler pipes and heater pipes extending toward the front of a vehicle body. In this manner, all the pipes are supported to a common bracket. Therefore, all the pipes can be held stably at predetermined positions of the air conditioning unit, and the number of components can be reduced thereby providing cost reduction.

With a seventh solution of the invention, in the vehicle air conditioner, the heater pipes include a supply pipe for supplying a heat medium for heat application to the heating heat exchanger, and a return pipe from the heat medium for heat application, the supply pipe and the return pipe are supported to the bracket so as to be arranged one above the other, and the cooler pipes are supported to the bracket below the heater pipes. Therefore, all the pipes and the bracket can be arranged compactly, and all the pipes can be firmly supported.

With an eighth solution of the invention, in the vehicle air conditioner, the bracket is formed to be separable on vertical center lines of all the cooler and heater pipes, and one separate piece of the bracket is formed integrally with the air conditioning unit, while the other separate piece is attached detachably to said one separate piece. This facilitates attachment and detachment of the cooler pipes and ensures alignment thereof

With a ninth solution of the invention, in the vehicle air conditioner, openings for cooler pipes formed in the bracket have a diameter with a predetermined clearance left from the outer diameter of the cooler pipes, the bracket includes a seal plate detachable with respect to the openings for cooler pipes, and the cooler pipes are fixed to the bracket by fitting the seal plate to the bracket.

Therefore, in detaching the expansion valve connected to the cooling heat exchanger and presented laterally from the side wall of the air conditioning unit, the above structure provides slight freedom of movement for the cooler pipes. As a result, the expansion valve can be detached easily without removal of the bracket, which facilitates detachment work.

With a tenth solution of the invention, in the vehicle air conditioner the seal plate has a groove for a cooler pipe, the groove has a width greater than the diameter of the cooler pipe and smaller than the diameter of the opening of the bracket, and the seal plate is detachable substantially at a right angle

with respect to the cooler pipe. Therefore, the seal plate can stably secure the cooler pipe to the bracket, and detachment of the seal plate can be easily carried out in a narrow space.

With an eleventh solution of the invention, in the vehicle air conditioner, the bracket has a flat surface opposed to the dash panel disposed at the front of the air conditioning unit, and the flat surface is capable of being pressed against the peripheries of the openings for heater pipes and the openings for cooler pipes in the dash panel. This provides improved sealing properties between the dash panel and the pipes, and excellent waterproof sound insulating and heat insulating properties. Furthermore, since the dash insulators surrounding the openings can be held by the flat surface, the dash insulators can be prevented from peeling.

With a twelfth solution of the invention, in the vehicle air conditioner, the cooler pipe is connected to the cooling heat exchanger through an expansion valve, the expansion valve is disposed adjacent the outer surface of a side wall of the air conditioning unit located toward the air blowing unit, an extended wall is formed integrally with the outer surface of the side wall to cover the periphery of the expansion valve, a cover is provided to cover the extended wall, and the expansion valve is capable of being covered with the extended wall and the cover.

With this configuration, the extended wall and the cover prevents the expansion valve from being exposed to the outside air without any special work such as tightly wrapping the expansion valve with rubber sealing member, which significantly improves workability. Furthermore, the expansion valve can be easily attached and detached.

With a thirteenth solution of the invention, in the vehicle air conditioner, the cooling heat exchanger is disposed so as to be inclined downwardly in a rear to front direction of a vehicle body, the cooling heat exchanger is provided with a plurality of flat tubes which are stacked in the widthwise direction of the vehicle to extend in the lengthwise direction of the vehicle body and through which a refrigerant flows, a corrugate fin is interposed between the adjacent flat tubes, and the lower end of the corrugate fin is located above the lower ends of the flat tubes.

With this configuration, condensate produced in the cooling heat exchanger can easily flow along the lower ends of the flat tubes in a rear to front direction of the vehicle body. Therefore, the condensate can be promptly recovered from the cooling heat exchanger, which significantly reduces that the condensate is transferred above the cooling heat exchanger.

With a fourteenth solution of the invention, in the vehicle air conditioner, a drain port is provided in a bottom wall part of the air conditioning unit, and the drain port is disposed at the same side of the air conditioning unit at which the cooler pipes and the heater pipes are arranged, in proximity to the cooler pipes and the heater pipes, and toward the front of the vehicle body. Therefore, the drain pipe can be arranged collectively with the heater and cooler pipes, which provides their compact layout. Furthermore, since the drain pipe and the heater and cooler pipes can be attached together to the dash panel, this improves workability of assembly and sealing properties between the pipes and the dash panel.

With a fifteenth solution of the invention, in the vehicle air conditioner a drain passage continuous with the drain port is provided, and the exit of the drain passage is extended, together with the cooler pipes and the heater pipes, from the side wall of the air conditioning unit located toward the air blowing unit. This enables effective use of a space between the air conditioning unit and the air blowing unit, and pro-

5

vides utilization of the opposite side wall of the air conditioning unit and extension of a space on the driver's seat side of the air conditioning unit.

With a sixteenth solution according to claim 16 of the invention, in the vehicle air conditioner e&Gclaim4i, a drain pipe is connected to the exit of the drain passage, and the drain pipe is disposed toward the front of the vehicle body. Therefore, the drain pipe, the heater pipes and the cooler pipes can be arranged collectively in the same direction toward the dash panel. This provides compact piping layout and significantly improves workability of attachment of the pipes to the dash panel.

With a seventeenth solution of the invention, in the vehicle air conditioner, the heating heat exchanger and the cooling heat exchanger are arranged substantially horizontally in the air conditioning unit with the heating heat exchanger located above the cooling heat exchanger, the cooling heat exchanger is inclined downwardly in a rear to front direction of the vehicle body, a lower space into which an air from the intermediate duct is introduced is provided under the cooling heat exchanger, a bottom wall part of the air conditioning unit is provided under the lower space, a drain port is formed in the bottom wall part integrally with the air conditioning unit, and a drain passage continuous with the drain port is extended from the side wall part of the air conditioning unit and disposed closer to the front of the vehicle body than the intermediate duct.

Therefore, the drain passage and the cooler pipes can be disposed between the air conditioning unit and the air blowing unit without interfering with the intermediate duct. In another aspect, the intermediate duct can be arranged to send an air from the air blowing unit to the air conditioning unit effectively without being affected by the drain passage and the cooler pipes.

With an eighteenth solution of the invention, in the vehicle air conditioner, the heater pipes and the cooler pipes are supported one above another to the bracket, and the drain pipe is disposed below the cooler pipes. Therefore, the heater and cooler pipes can be disposed in a compact and collective arrangement.

With a nineteenth solution of the invention, in the vehicle air conditioner, an attachment part through which the air conditioning unit is attached to a dash panel disposed at the front of the air conditioning unit is provided integrally with the drain passage in proximity to the exit of the drain passage. This increases the rigidity of surroundings of the drain passage, and enables the drain passage to be attached stably at a predetermined position of the dash panel thereby increasing the precision of assembly. position of the dash panel thereby increasing the precision of assembly.

With a twentieth solution of the invention, in the vehicle air conditioner, a bottom wall part of the air conditioning unit has an inclined surface that is lowest in level at the drain port, is highest in level at the corner diagonally opposite to the drain port and is thus gradually downwardly inclined from the diagonally opposite corner toward the drain port. Therefore, condensate in the air conditioning unit can be smoothly guided to the drain port.

With a twenty-first solution of the invention, in the vehicle air conditioner, the intermediate duct has an inclined duct connected to the air blowing unit and inclined obliquely downwardly from the air blowing unit toward the air conditioning unit, and a horizontal duct connected with the inclined duct and the air conditioning unit to form a substantially horizontal air passage.

With this configuration, an air flowing through the intermediate duct is smoothly changed in direction from an

6

obliquely downward flow to an approximate horizontal flow and then introduced into the air conditioning unit. Therefore, the air flow colliding with the bottom wall part is significantly reduced, resulting in providing an excellent function of preventing condensate in the bottom wall part from being involved into the air flow.

With a twenty-second solution of the invention, in the vehicle air conditioner, the bottom wall part of the air conditioning unit has an inclined surface that is lowest in level at the drain port, is highest in level at the corner diagonally opposite to the drain port and is thus gradually downwardly inclined from the diagonally opposite corner toward the drain port, the middle of the bottom wall part is provided with a fiat surface portion, and the drain passage is also inclined downwardly from the drain port toward the exit of the drain passage. Therefore, an air introduced into the air conditioning unit is better separated from condensate guided to the drain port, resulting in a prompt discharge of the condensate and a smooth air flow.

With a twenty-third solution of the invention, in the vehicle air conditioner, a rib is provided in a standing manner on the bottom wall part of the air conditioning unit and along the flowing direction of the air introduced through the intermediate duct, and the drain port is provided in a portion of the bottom wall part closer to the front of the vehicle body than the rib.

With this configuration, the rate of air flow sent from the intermediate duct to the air conditioning unit is smaller in the portion of the bottom wall part closer to the front of the vehicle body than the rib. Therefore, condensate can be effectively prevented from being taken into the cooling heat exchanger located above by the air flow.

With a twenty-fourth solution of the invention, in the vehicle air conditioner, the heating heat exchanger and the cooling heat exchanger are arranged substantially horizontally in the air conditioning unit with the heating heat exchanger located above the cooling heat exchanger, the cooling heat exchanger is inclined downwardly in a rear to front direction of the vehicle body, a lower space into which an air from the intermediate duct is introduced is provided under the cooling heat exchanger, a bottom wall part of the air conditioning unit is provided under the lower space, the cooling heat exchanger is inclined downwardly in a rear to front direction of the vehicle body, the intermediate duct has an approximately triangular section at a connected portion with the lower space, the intermediate duct has an inclined duct inclined obliquely downwardly from the air blowing unit toward the air conditioning unit, and a horizontal duct connected from the inclined duct to the air conditioning unit to form a substantially horizontal air passage, the inclined duct has an approximately rectangular section at a connected portion with the air blowing unit, and the inclined duct has an approximately triangular section at a connected portion with the horizontal duct.

With this configuration, air smoothly flows through the intermediate duct, a partial air flowing through one side of the horizontal duct having a larger sectional area, i.e., a portion thereof located toward the rear of the vehicle body, is introduced at high speed into the air conditioning unit, and a partial air flowing through the other side of the horizontal duct is introduced at low speed into the air conditioning unit. Therefore, the high-speed air flow inside of the air conditioning unit is smoothly introduced to the cooling heat exchanger, resulting in improved heat exchanger effectiveness.

With a twenty-fifth solution of the invention, in the vehicle air conditioner, the air conditioning unit is provided with a temperature control damper for controlling the temperature

of a conditioned air by changing the ratio of the flow rate of air passing through the heating heat exchanger to the flow rate of air introduced into the air conditioning unit, and a blow-out direction switching damper for changing the blow-out direction of the conditioned air, and drive mechanisms and actuators for driving the temperature control damper and the blow-out direction switching damper, respectively, are disposed on the side wall of the air conditioning unit located toward the air blowing unit.

With this configuration, an air from the air blowing unit smoothly flows through the intermediate duct, is introduced into the lower space of the air conditioning unit, is turned upward, and then passes through the cooling and heating heat exchangers. During the time, the temperature control damper is driven by the actuator via the drive mechanism, the temperature of the conditioned air is controlled by changing the ratio of the flow rate of air passing through the heating heat exchanger to the flow rate of air introduced into the air conditioning unit. The conditioned air produced in this manner is changed in blow-out direction by the blow-out direction switching damper, and then supplied to a desired place in the passenger's room.

In this case, the drive mechanisms and actuators for the two dampers are disposed on the side wall of the air conditioning unit located toward the air blowing unit, and collected in a dead space between the air blowing unit and the air conditioning unit which are spaced apart from each other by a distance between both ends of the intermediate duct. This makes the air conditioner more compact and reduces its installation space. Furthermore, collective arrangement of the two actuators decreases the number of processes for assembly of the air conditioning unit and the number of processes for attachment thereof to the vehicle body.

With a twenty-sixth solution of the invention, in the vehicle air conditioner the temperature control damper is formed of two damper members, and control of swing motions of the two damper members allows the ratio of the flow rate of air passing through the heating heat exchanger to be changed thereby controlling the temperature of the conditioned air.

In general, to increase the area of the air passage for introduction of air into the heating heat exchanger or bypassing of the heating heat exchanger, it is required to provide a large-area temperature control damper for swing motion. This involves increasing the distance between the cooling and heating heat exchangers, resulting in increased height of the air conditioning unit. Unlike this, in this invention, the temperature control damper between the cooling and heating heat exchangers is formed of two damper members. Therefore, the area of the air passage for introduction of air into the heating heat exchanger or bypassing of the heating heat exchanger can be increased without the space between both the heat exchangers being increased.

With a twenty-seventh solution of the invention, in the vehicle air conditioner, the two damper members are controlled to differ from each other in their opening/closing timings at which air passages toward the heating heat exchanger are opened or shut off. This provides precise temperature control.

With a twenty-eighth solution of the invention, in the vehicle air conditioner of any one, the air blowing unit is provided with an inside/outside air switching damper for controlling the amount of air taken in from the outside of a passenger's room and the amount of air taken in from the inside of the passenger's room, and an actuator for driving the inside/outside air switching damper is disposed on a side wall of the air blowing unit located toward the air conditioning unit.

Thus, the actuator for the inside/outside air switching damper is disposed on the side wall of the air blowing unit located toward the air conditioning unit, i.e., in a dead space between both the units, like the drive mechanisms and actuators for the air conditioning unit. This further reduces the size of the air conditioner, the number of processes for assembly of the units and the number of processes for attachment of the units to the vehicle body.

With a twenty-ninth solution of the invention, in the vehicle air conditioner, the air conditioning unit is divided into upper and lower casings and the upper casing is divided into right and left parts, and the cooling heat exchanger and the heating heat exchanger are held sandwiched between the two divided parts of the upper casing.

With this configuration, the cooling and heating heat exchangers can be easily assembled and securely held. Furthermore, since no vertically separated surface is formed in the lower casing, this eliminates fear of leakage of condensate and provides ensured discharge of condensate through the drain port.

With a thirtieth solution of the invention, in the vehicle air conditioner, a dash panel forming a partition for separating the air conditioning unit from an engine room is provided at the side of the air conditioning unit located toward the front of the vehicle body, and the drain port is provided in a portion of the lower casing located toward the air blowing unit and toward the front of the vehicle body, the drain passage is extended from the drain port toward the air blowing unit substantially in parallel with the dash panel to protrude from the air conditioning unit, a drain pipe is connected to the exit of the drain passage, the drain pipe is extended in a direction orthogonal to the dash panel and inserted into an opening in the dash panel, and the drain passage is formed of an elongated-groove part formed integrally with the lower casing, and a cover for the elongated groove part formed integrally with the upper casing.

With this configuration, the drain passage is formed not as a hollow body but as an elongated groove part in the lower casing, and a separate member covers the upper surface of the groove part. This enables integral formation of the drain passage with the lower casing and easy formation thereof even if the depth and length of the elongated groove are rather large, provides flexibility to the shape and size of the drain passage, ensures a space for storing condensate, and provides a configuration of the space that can discharge condensate smoothly.

A thirty-first solution of the invention is directed to a vehicle air conditioner comprising: an air conditioning unit disposed substantially in the middle of the inside of an instrument panel in a widthwise direction of a vehicle; an air blowing unit- disposed to a front-passenger's side of the air conditioning unit; an intermediate duct for ducting an air from the air blowing unit to the air conditioning unit; and a cooling heat exchanger and a heating heat exchanger disposed in the air conditioning unit, in which the air introduced from the intermediate duct into the air conditioning unit is allowed to pass through the cooling and heating heat exchangers disposed in the air conditioning unit to produce a conditioned air. Further, a drain port is provided in a bottom wall part of the air conditioning unit, the drain port is disposed in a portion of the bottom wall part located toward the front of the vehicle body and along a side wall of the air conditioning unit, and cooler pipes for the cooling heat exchanger are arranged along the same side wall that the drain port is located.

With this configuration, the drain port and the cooler pipes are disposed at the same side of the air conditioning unit. This facilitates the alignment and attachment work in attaching the

air conditioning unit to the dash panel. Since the drain pipe connected to the drain port and the cooler pipes are arranged in proximity to each other, this makes the air conditioning unit more compact.

A thirty-second solution of the invention is directed to a vehicle air conditioner comprising: an air conditioning unit disposed substantially in the middle of the inside of an instrument panel in a widthwise direction of a vehicle; an air blowing unit disposed to a front-passenger's side of the air conditioning unit; an intermediate duct for ducting an air from the air blowing unit to the air conditioning unit; and a cooling heat exchanger and a heating heat exchanger disposed in the air conditioning unit, in which the air introduced from the intermediate duct into the air conditioning unit is allowed to pass the cooling and heating heat exchangers disposed in the air conditioning unit to produce a conditioned air. Further, a drain port is provided in a bottom wall part of the air conditioning unit, a drain passage connected integrally with the drain port is disposed to extend laterally of the air conditioning unit, a drain pipe is connected to the exit of the drain passage, and the drain pipe is disposed to extend into an engine room.

With this configuration, the drain passage is disposed to extend laterally from the projecting plane of the air conditioning unit as viewed in a vertical direction, and the drain pipe is connected to the exit of the drain passage. Therefore, there is no need for alignment of the opening of the dash panel and the drain port in a front to rear direction of the vehicle body, and their positional relationship can be set freely by changing the length of the drain passage, which provides great design flexibility.

Furthermore, since the drain passage can form a space for storing condensate, this reduces the amount of condensate stored in the bottom wall part and substantially eliminates involvement of condensate into the air flow being introduced into the cooling heat exchanger.

A thirty-third solution of the invention is directed to a vehicle air conditioner comprising: an air conditioning unit disposed substantially in the middle of the inside of an instrument panel in a widthwise direction of a vehicle; an air blowing unit disposed to a front-passenger's side of the air conditioning unit; and an intermediate duct for ducting an air from the air blowing unit to the air conditioning unit, in which the air introduced from the intermediate duct into the air conditioning unit is allowed to pass through a cooling heat exchanger and a heating heat exchanger juxtaposed one above the other in the air conditioning unit to produce a conditioned air. Further, a drain port is provided in a bottom wall part of the air conditioning unit the drain port is disposed in a portion of the bottom wall part located toward the front of the vehicle body and along a side wall of the air conditioning unit, and cooler pipes for the cooling heat exchanger are arranged along the same side wall that the drain port is located.

With this configuration, like the solution the air conditioning unit can be easily attached to the dash panel and can be made more compact.

A thirty-fourth solution of the invention is directed to a vehicle air conditioner comprising: an air conditioning unit disposed substantially in the middle of the inside of an instrument panel in a widthwise direction of a vehicle; an air blowing unit disposed to a front-passenger's side of the air conditioning unit; and an intermediate duct for ducting an air from the air blowing unit to the air conditioning unit, in which the air introduced from the intermediate duct into the air conditioning unit is allowed to pass through a cooling heat exchanger and a heating heat exchanger juxtaposed one

above the other in the air conditioning unit to produce a conditioned air. Further, a drain port is provided in a bottom wall part of the air conditioning unit, a drain passage connected integrally with the drain port is disposed to extend laterally of the air conditioning unit, a drain pipe is connected to the exit of the drain passage, and the drain pipe is disposed to extend into an engine room.

This configuration, like the solution provides significantly improved design flexibility to the drain port and the opening of the dash panel, and enables condensate to be stored in the drain passage to prevent roll-up of condensate.

With a thirty-fifth solution of the invention, in the vehicle air conditioner, the side wall of the air conditioning unit at which the drain passage is disposed is at the side of the air conditioning unit located toward the air blowing unit. Therefore, the space between the air conditioning unit and the air blowing unit can be effectively used. Furthermore, a space located laterally from the air conditioning unit and opposite to the air blowing unit, i.e., a space on the driver's side of the air conditioning unit, can be obtained amply. Alternatively, a large-sized temperature-control duct can be provided on the driver's side wall of the air conditioning unit to effectively carry out the temperature control on the passenger's room.

With a thirty-sixth solution of the invention, in the vehicle air conditioner, a bracket for supporting the cooler pipes is formed integrally with the air conditioning unit, and portions of the cooler pipes connected to the cooling heat exchanger, extended from the side wall of the air conditioner, bent substantially at a right angle and extended toward the front of the vehicle body are attached to the bracket. Therefore, the cooler pipes can be held stably at predetermined positions of the air conditioning unit.

With a thirty-seventh solution of the invention, in the vehicle air conditioner, the bracket is formed to be separated on vertical lines passing through the middles of the cooler pipes in their radial direction, and one separate piece of the is formed integrally with the air conditioning unit, while the other separate piece is attached detachably to said one separate piece. This facilitates attachment and detachment of the cooler pipes and ensures alignment thereof.

With a thirty-eighth solution of the invention, in the vehicle air conditioner, openings for cooler pipes formed in the bracket have a diameter with a predetermined clearance left from the outer diameter of the cooler pipes, and the cooler pipes are fixed to the bracket by fitting a seal plate to the bracket, the seal plate being disposed detachably from the bracket. Therefore, in detaching the expansion valve connected to the cooling heat exchanger and presented laterally from the side wall of the air conditioning unit, the above structure provides slight freedom of movement for the cooler pipes. As a result, the expansion valve can be detached easily without removal of the bracket, which facilitates detachment work.

With a thirty-ninth solution of the invention, in the vehicle air conditioner, openings for cooler pipes formed in the bracket have a diameter with a predetermined clearance left from the outer diameter of the cooler pipes, and the cooler pipes are fixed to the bracket by fitting a seal plate to the bracket, the seal plate being disposed detachably from the bracket. Therefore, the same effects as in the above solution according to claim 38 can be obtained.

With a fortieth solution of the invention, in the vehicle air conditioner the seal plate has a groove corresponding to a cooler pipe, the groove has a width greater than the diameter of the cooler pipe and smaller than the diameter of the opening of the bracket, and the seal plate is detachable substan-

11

tially at a right angle with respect to the cooler pipe. Therefore, the seal plate can stably secure the cooler pipe to the bracket.

With a forty-first solution of the invention, in the vehicle air conditioner, the seal plate has a groove corresponding to a cooler pipe, the groove has a width greater than the diameter of the cooler pipe and smaller than the diameter of the opening of the bracket, and the seal plate is detachable substantially at a right angle with respect to the cooler pipe. Therefore, the same effect as in the above solution according can be obtained.

With a forty-second solution of the invention, in the vehicle air conditioner, the drain port is disposed in a portion of the bottom wall part of the air conditioning unit located toward the front-passenger's seat and toward the front of the vehicle body, and the drain passage is disposed at the side wall of the air conditioning unit located toward the front-passenger's seat to extend from the air conditioning unit. In this manner, the drain port is open at a position that is not susceptible to the air flow sent from the intermediate duct to the air conditioning unit, and condensate is guided to the drain passage which is outside of the projecting plane of the air conditioning unit. This prevents condensate from being involved into the cooling heat exchanger.

With a forty-third solution of the invention, in the vehicle air conditioner the bottom wall part of the air conditioning unit has an inclined surface that is lowest in level at the drain port, is highest in level at the corner diagonally opposite to the drain port and is thus gradually downwardly inclined from the diagonally opposite corner toward the drain port, and the drain passage is also inclined downwardly from the drain port toward the exit of the drain passage. Therefore, condensate can be promptly collected to the drain port and guided to the exit of the drain passage.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a perspective view in appearance of an air conditioner according to an embodiment of the present invention as seen from the left rear.

FIG. 2 is a perspective view in appearance of the air conditioner as seen from the right rear.

FIG. 3 is a rear view in appearance of the air conditioner.

FIG. 4 is an illustration of how the air conditioner is disposed in a vehicle.

FIG. 5 schematically illustrates the structure of the air conditioner and corresponds to FIG. 3.

FIG. 6 is a sectional view of an air conditioning unit showing its internal structure.

FIG. 7 is an illustration of how an evaporator is disposed.

FIG. 8 shows sectional configurations of flat tubes and corrugate fins in the evaporator of FIG. 7.

FIG. 9 is a front view in appearance of the air conditioning unit.

FIG. 10 illustrates how heater pipes and cooler pipes are attached to the air conditioning unit.

FIG. 11 is a view of the attachment of the heater and cooler pipes of FIG. 8 as seen from the opposite direction.

FIG. 12 is a view of the air conditioner as seen from the air blowing unit side, wherein the air conditioning unit is attached to a dash panel.

FIG. 13 is a perspective view of a bottom wall part of the air conditioning unit as seen from the left rear.

FIG. 14 is a perspective view of the bottom wall part of the air conditioning unit as seen from the right front.

FIG. 15 is a plan view of the bottom wall part of the air conditioning unit.

12

FIG. 16 is a front view of the bottom wall part of the air conditioning unit.

FIG. 17 is a side view of the bottom wall part of the air conditioning unit.

FIG. 18 is a perspective view of an intermediate duct.

FIG. 19 is a perspective view of an air conditioner for a left-hand drive car.

FIG. 20 is a perspective view of an air conditioning unit of the air conditioner of FIG. 19.

FIG. 21 is a partly enlarged view of a bracket of the air conditioning unit of FIG. 20 and illustrates how the heater pipes and cooler pipes are attached to the bracket.

FIG. 22 is a view of the bracket of FIG. 21 seen from the opposite direction.

FIG. 23 is a view of the air conditioning unit of the air conditioner of FIG. 19 as seen from the engine room side.

FIG. 24 illustrates how an expansion valve box is attached to a casing.

BEST MODE FOR CARRYING OUT THE INVENTION

Preferred embodiments of the present invention will be described below with reference to the drawings.

FIGS. 1 to 3 shows the appearance of an air conditioner 1 according to a preferred embodiment of the present invention. This air conditioner 1 is housed inside of an instrument panel 2 disposed in a passenger's room of a car, as shown in FIG. 4. This car is a so-called right-hand drive car in which a driver's seat and a front passenger's seat are located at the right and left sides of the vehicle body, respectively. A dash panel P (as shown in FIGS. 6 and 10) separates an engine room located at the front of the vehicle body from the front side of the passenger's room. It should be noted herein that the vehicle body front and vehicle body rear of the air conditioner 1 are referred to as the front and rear of the air conditioner 1.

As shown in FIG. 3, the air conditioner 1 essentially consists of an air blowing unit 3, an air conditioning unit 4 for cooling an air from the air blowing unit 3, controlling the temperature of the air and then supplying the air to the passenger's room, and an intermediate duct 5 through which the air from the blowing unit 3 is sent to the air conditioning unit 4. The air conditioning unit 4 is disposed substantially in the widthwise middle of the car, while the air blowing unit 3 is disposed a predetermined distance leftward away from the air conditioning unit 4 and to the front of the front passenger's seat. The bottom end of the air blowing unit 3 is located at an upper level than the bottom end of the air conditioning unit 4 to ensure an ample legroom for the front-seat passenger.

The air blowing unit 3 includes a casing 6 divided into right and left parts substantially at the car widthwise middle, and the two parts are integrated into a single piece using a fastener or the like. The upper portion of the casing 6 includes an air intake part 7 for taking an air into the air conditioner 1. The lower portion of the casing 6 includes an air blowing part 8 for sending the intake air to the air conditioning unit 4. The upper portion of the air intake part 7 is formed with an outside air intake 10 through which an air outside of the passenger's room is taken in via a duct (not shown), and an inside air intake 11 through which an air inside of the passenger's room is taken in. Further, inside of the air intake part 7, an inside/outside air switching damper 12 is provided to make one of the inside and outside air intakes 10 and 11 open and the other closed.

More specifically, the upper portion of the air intake part 7 has a front wall of rectangular shape that inclines toward the rear of the vehicle body in proceeding to the top and a rear

13

wall of rectangular shape that inclines toward the front of the vehicle body in proceeding to the top. The front and rear walls are continuous at their upper edges so that the upper portion of the air intake part 7 has an approximately triangular section when viewed in the car widthwise direction. The front and rear walls have the outside and inside air intakes 10 and 11 opened in rectangular shape, respectively. Each air intake is formed integrally with a grille 13. The side walls of the air intake part 7 connect the corresponding side edges of the front and rear walls. The inside/outside air switching damper 12 is of rectangular shape larger than each of the air intakes 10 and 11, and has a shaft that is located at its upper edge and extends in the car widthwise direction. Both ends of the shaft are supported to the upper ends of the pair of side walls of the air intake part 7.

The lower end of the inside/outside air switching damper 12 is provided with a connecting part (not shown) passing through one of the side walls of the air intake part 7 so as to be connected with an output shaft of an actuator 15 attached to that side wall of the air intake part 7. This side wall is formed integrally with a boss to which the actuator 15 is fastened with screws. The actuator 15 operates in response to a signal from an air conditioning controller (not shown) disposed in the vehicle body. A signal line from the air conditioning controller is connected with a coupler 17 for the actuator 15.

When the actuator 15 angularly moves the inside/outside air switching damper 12 about the shaft to the position that the outside air intake 10 is fully open, the inside air intake 11 is fully closed. Thus, the air blowing unit 3 enters an outside air intake mode in which only an outside air is taken in the unit. On the other hand, when the actuator 15 angularly moves the inside/outside air switching damper 12 oppositely from that position to the position that the outside air intake 10 is fully closed, the inside air intake 11 is fully open. Thus, the air blowing unit 3 enters an inside air circulation mode.

As shown in FIG. 5, the lower portion of the air intake part 7 is provided with a filter accommodation part 21 for accommodating a filter 20 for filtering the intake air. Although not shown, an opening is formed in a portion of the casing 6 located to the rear side of the filter accommodation part 21, which enables the filter 20 to be replaced with new one through the opening. The air blowing part 8 is located under the filter accommodation part 21. In the air blowing part 8, a centrifugal multi-blade fan is placed as an air blowing fan 23 to extend its rotating shaft vertically, and a fan-driving motor 24 is disposed below the air blowing fan 23. As shown in the arrows in FIG. 5, the rotation of the air blowing fan 23 causes air to be taken in from above the air intake part 7, to pass through the filter 20 and to be introduced into the air blowing part 8.

The right wall of the air blowing part 8 is formed with an opening 8a and is connected at the opening 8a to the left end of the intermediate duct 5. The air blowing and air conditioning units 3 and 4 are located away from each other by a distance between both ends of the intermediate duct 5. As shown in the arrow in FIG. 5, the air from the air blowing unit 3 is smoothly sent into the air conditioning unit 4 by passing through the intermediate duct 5.

As shown in FIG. 5 again, the intermediate duct 5 has an inclined duct 5a and a horizontal duct 5b. The inclined duct 5a is formed to obliquely downwardly extend from the left end of the intermediate duct 5 toward the bottom end of the air conditioning unit 4. The horizontal duct 5b is communicated at its right end with the inside of the air conditioning unit 4 through an opening 25 formed at the bottom end side of a casing 30 for the air conditioning unit 4.

14

As shown in FIG. 18, the inclined duct 5a is formed to have an approximately rectangular section at its left end and an approximately triangular section at its right end and smoothly change its cross-sectional shape from rectangle to triangle thereby reducing air turbulence and air resistance. The horizontal duct 5b continues to have an approximately triangular section and is internally provided with a plurality of projections to straighten the air flow. The horizontal duct 5b and the opening 25 of the casing 30 are connected at their similar triangular sections with each other.

In particular, a high-speed air in the radically outer side (the vehicle body rear side) of the air blowing unit 3 is sent to a wider area side (the vehicle body rear side) of the opening 25 of substantially triangular shape, while a low-speed air in the radically inner side (the vehicle body front side) of the air blowing unit 3 is sent to a narrower area side (the vehicle body front side) of the opening 25 of substantially triangular shape.

As shown in FIG. 2, the intermediate duct 5 is provided at its top wall with a control circuit 26 for changing the rpm of the fan-driving motor 24. The control circuit 26 is provided at its top with a coupler 27 to which a connector from the air conditioning controller is connected.

The air conditioning unit 4 has the casing 30 which is generally vertically elongated and formed in a rectangular box of larger size than that of the casing 6 for the air blowing unit 3. The casing 30 is divided into a bottom wall part 31 and a body part 32 one above the other; the bottom wall part 31 forms a lower casing and the body part 32 forms an upper casing. Further, the body part 32 is divided into two portions substantially at the middle in the widthwise direction of the car, like the air blowing unit 3.

As shown in FIG. 6, inside of the casing 30, an evaporator 33 as an element of a refrigeration cycle is placed above the opening 25 at which the casing 30 is connected to the intermediate duct 5, and a heater core 34 is placed above the evaporator 33. The upper portion of the casing 30 is formed with a plurality of air outlets for a conditioned air. As shown in the arrows in FIG. 5, the air flow from the air blowing unit 3 turns an upward flow in the air conditioning unit 4.

The evaporator 33 is a cooling heat exchanger for cooling the air from the air blowing unit 3. The evaporator 33 is formed by stacking multiple flat tubes 33a, each made of a thin metal plate such as an aluminum plate, in parallel and interposing a corrugate fin 33b made of a thin metal plate between the adjacent flat tubes 33a. As shown in FIGS. 7 and 8, the flat tube 33a is a hollow body formed by superposing halved containers one on another in opposed relation to extend in a rear to front direction of the vehicle body. The corrugate fin 33b interposed between the flat tubes 33a is formed to have a wave shape when viewed from above. The bottom end of the corrugate tube 33b is located above the bottom ends of the adjacent flat tubes 33a. In other words, the bottom ends of the flat tubes 33a are located below the bottom ends of the corrugate fins 33b. Therefore, a space between the bottom ends of the adjacent flat tubes 33a functions as a space for guiding condensate falling from the corrugate fin 33b down to the bottom end surface of the flat tube 33a in a rear to front direction of the vehicle body.

The flat tubes 33a of the evaporator 33 are constructed so that a low-temperature refrigerant produced by refrigeration cycle circulates therein to cool the air passing upwardly through the evaporator 33. Specifically, although not shown, tanks are provided at both sides of the evaporator 33 adjacent to both ends of all the flat tubes 33a to communicate with the tubes. One of the tanks is divided into an inflow tank section and an outflow tank section by a partition plate disposed at the middle thereof in a stacking direction of the flat tubes 33a.

15

The refrigerant flowing into the inflow tank section flows into the other tank through upstream tubes connected to the inflow tank section, and then flows into the outflow tank section of said one tank through downstream tubes.

The evaporator 33 is placed to extend the tubes in the car lengthwise direction and to locate portion thereof closer to the rear of the car at higher level, thereby passing all the air from the air blowing unit 3 through the evaporator 33. The inflow and outflow tank sections of the evaporator 33 are connected with corresponding cooler pipes 90. Each cooler pipe 90 is provided so as to be extended outwardly from a left side wall 30a (shown in FIG. 5) of the casing 30 for the air conditioning unit 4, bent substantially at a right angle and then extended toward the front of the vehicle body.

The heater core 34 is horizontally placed above the evaporator 33 to apply heat to the air from the evaporator 33. The heater core 34 is connected with heater pipes 91 including introduction and discharge pipes for a high-temperature engine cooling water. Each heater pipe 91 is provided so as to be extended outwardly from the left side wall 30a (shown in FIG. 5) of the casing 30 for the air conditioning unit 4, bent substantially at a right angle, and then extended toward the front of the vehicle body. The heater pipes 91 and cooler pipes 90 are supported to the air conditioning unit 4 by a bracket 92.

Next, description will be made about the bracket 92 and its surroundings with reference to FIGS. 9 to 12. The heater pipes 91 are juxtaposed one above the other. One of the cooler pipes 90 is arranged immediately below the heater pipe 91, while the other is arranged below said one cooler pipe 90 and slightly off to the side. The bracket 92 includes a fixed bracket 92a integrally formed with the casing 30 in the air conditioning unit 4 and a detachable bracket 92b. The vertical plane that divides the bracket 92 into the fixed and detachable brackets 92a and 92b runs through the vertical center lines of the heater tubes 91 and the cooler tubes 90.

The fixed and detachable brackets 92a and 92b of the bracket 92 have recesses corresponding to arcs obtained by halving the heater pipes 91 and cooler pipes 90, and the recesses form openings 94 and 95 for the heater pipes 91 and cooler pipes 90 when both the brackets 92a and 92b are abutted on each other. The diameter of the opening 94 for the heater pipe 91 is substantially equal to the outer diameter of the heater pipe 91. Therefore, when the detachable bracket 92b is attached to the fixed bracket 92a, the heater pipes 91 can be fixed in the openings 94.

On the other hand, the opening 95 for the cooler pipe 90 is formed with a predetermined clearance left from the outer diameter of the cooler pipe 90. In this manner, when the detachable bracket 92b is attached to the fixed bracket 92a, the cooler pipes 90 can be moved slightly. Therefore, at the attachment and detachment of an expansion valve box 96 for the evaporator 33 to and from the left side wall 30a of the casing 30, the expansion valve box 96 can be attached and detached, without removal of the evaporator 33 from the casing 30, by slightly moving the cooler pipe 90.

To support the cooler pipes 90 to the bracket 92, seal plates 93 are provided. Each seal plate 93 has a half-round recess 97 of corresponding diameter to the outer diameter of the cooler pipe 90, and is laterally slidable by being guided in an elongated groove provided in the detachable bracket 92b. The cooler pipe 90 can be fixed to the bracket 92 by inserting the corresponding seal plate 93 to a predetermined position of the detachable bracket 92b. When the seal plate 93 is inserted in the groove to the predetermined position, a lug 98 on a plate 99 integrally formed with the seal plate 93 is fitted into a recess (not shown) of the detachable bracket 92b. On the other hand, in slidably pulling the seal plate 93 out of the groove,

16

the plate 99 need only be pinched to disengage the lug 98 from the recess and in this state, slid out of the groove. Thus, the seal plate 93 can be easily inserted into and pulled out of the groove.

It will be understood that the detachable bracket 92b can be attached to the fixed bracket 92a by screw fixation B in the same direction as with its assembly.

In this embodiment, the seal plates 93 are provided individually for the cooler pipes 90. However, a single seal plate may be provided for both the cooler pipes 90. Further, seal plates may also be provided for the heater pipes 91 and a drain pipe 83 to fix them.

Next, description will be made about a structure for discharging condensate in the air conditioning unit 4. Condensate produced in the evaporator 33 during air cooling is discharged outside through a drain 35 provided in the bottom wall part 31 of the casing 30. As shown in FIGS. 13 to 17, the drain 35 includes a drain port 80 and a drain passage 81 formed at the front-end left corner (the air blowing unit side) of the bottom wall part 31. The drain port 80 is formed integrally with the bottom wall part 31, and the drain passage 81 is formed integrally with the drain port 80. The drain passage 81 extends from the drain port 80 toward the air blowing unit substantially in parallel with the dash panel. The exit 82 of the drain passage 81 extends beyond the left side wall 30a of the casing 30 in the air conditioning unit 4 leftward (toward the air blowing unit). The exit 82 is connected with the drain pipe 83 substantially at a right angle. The end of the drain pipe 83 is inserted into a through hole 102 in the dash panel P.

The bottom wall part 31 has an inclined surface that is lowest in level at the drain port 80, is highest in level at the corner diagonally opposite to the drain port 80 and is thus gradually downwardly inclined from the diagonally opposite corner toward the drain port 80. The drain passage 81 is also inclined downwardly from the drain port 80 toward the exit 82. Such a configuration guides condensate stored in the bottom wall part 31 to flow toward the drain port 80, then flow toward the exit 82 through the drain passage 81, and then flow out of the passenger's room through the drain pipe 83.

Particularly, the inclined surface of the bottom wall part 31 of the casing 30 is branched into two and then merged at the left end of the bottom wall part 31 so that the left end is located at a lower level with respect to the right end of the horizontal duct 5b. With this configuration, even if a moving vehicle tilts on the front passenger's side, condensate stored in the bottom wall part 31 can be prevented from flowing back to the air blowing unit through the intermediated duct 5.

The intermediate duct 5 is connected with the air blowing unit 3 and, as shown in FIG. 5, has an inclined duct 5a and a horizontal duct 5b. The inclined duct 5a is inclined obliquely downward from the air blowing unit 3 toward the air conditioning unit 4. The horizontal duct 5b communicates the inclined duct 5a with the casing 30 of the air conditioning unit 4. The inclined duct 5a is formed separately from the horizontal duct 5b, while the horizontal duct 5b is formed integrally with the casing 30. Specifically, the lower half of the horizontal duct 5b is formed integrally with the bottom wall part 31, while the upper half thereof is formed integrally with the body part 32.

As shown in FIG. 18, the inclined duct 5a is formed to have an approximately rectangular section at a connected portion with the opening 8a of the air blowing part 8 in the air blowing unit 3 and an approximately triangular section at a connected portion with the horizontal duct 5b. In the inclined duct 5a, the air flows while smoothly changing its flow direction from

the condition that it flows through the rectangular sectional area to the condition that it flows through the triangular sectional area.

In this embodiment, since the horizontal duct **5b** is formed integrally with the casing **30** but separately from the inclined duct **5a**, the inclined duct **5a** can be easily designed and formed so that the air smoothly flows therein.

When the air flow is sent from the inclined duct **5a** directly into an introduction part **39** of the casing **30**, the downwardly inclined air flow will collide with the bottom wall part **31** to disturb or roll up condensate in the bottom wall part **31**. To cope with this, the horizontal duct **5b** is provided immediately before the introduction part **39** in this invention. Thus, the air flow that is sent obliquely downwardly from the air blowing unit **3** through the inclined duct **5a** is slightly changed substantially horizontally by the horizontal duct **5b** so as to be guided into the lower space **39** located below the evaporator **33** through the opening **25** of the air conditioning unit **4**. This suppresses the air flow directing obliquely downwardly in the lower space **39**, minimizes the collision of the air flow with the bottom wall part **31**, and prevents the roll-up of the condensate flowing in the bottom wall part **31**.

Particularly, the middle of the bottom wall part **31** is formed with a flat surface portion **31a** which is substantially parallel with the horizontal duct **5b**. With such a configuration, the air from the intermediate duct **5** flows along the flat surface portion **31a** in the lower space **39** and is changed in flow direction toward the evaporator **33** located above the flat surface portion **31a**. This effectively avoids the collision of the air flow coming into the lower space **39** with the condensate flow on the inclined surface of the bottom wall part **31** toward the drain port **80**, and significantly reduces the interference of the air flow with the condensate flow.

Further, the air from the air blowing unit **3** to the opening **25** through the intermediate duct **5** is sent from the inclined duct **5a** into the lower space **25** of the air conditioning unit **4** while its flow direction is changed substantially horizontally by the horizontal duct **5b** of substantially triangular section. The distribution of air flow rate at the time shows that a high-speed air in the radially outer side of the air blowing unit **3** flows through the vehicle body rear side of the horizontal duct **5b**, i.e., the wider sectional area of substantially triangular shape in the horizontal duct **5b**, and is sent to the casing **30**. In other words, a high-speed air flows through the vehicle body rear side, while a relatively low-speed air flows through the narrower sectional area of substantially triangular shape in the horizontal duct **5b**, i.e., the vehicle body front side of the horizontal duct **5b**. Therefore, it can be minimized that the air flow interferes with the condensate flow collected to the drain port **80** located toward the vehicle body front.

Portions of the cooling heat exchanger **33** through which the high-speed air passes are located toward the rear of the vehicle body and are located at the higher side of the obliquely inclined heat exchanger **33**. The condensate produced in the cooling heat exchanger **33** falls down on the outer surfaces of the flat tubes **33a** and the corrugate fins **33b**, and flows directly on the bottom surfaces of the corrugate fins and flat tubes from the vehicle body rear side to the vehicle body front side of the heat exchanger. Otherwise, the condensate flows from the bottom surfaces of the corrugate fins **33b** to the bottom surfaces of the flat tubes **33a** and then flows on the bottom surfaces of the flat tubes **33a** from the vehicle body rear side to the vehicle body front side of the heat exchanger. Thereby, it can be largely suppressed that the condensate produced in the cooling heat exchanger is introduced above the cooling heat exchanger, i.e., into the heating heat exchanger, by the high-speed air flow.

The condensate tends to flow into the vehicle body front side of the cooling heat exchanger, i.e., the lower side thereof. The air flow in this side, however, is at a relatively low rate, and the air flow has a lower rate and approximates a flow rate of zero with approach to the front of the heat exchanger. Therefore, the possibility that the condensate collected at the front side of the cooling heat exchanger is introduced into the heating heat exchanger by the air flow is extremely low.

Further, the cooling heat exchanger has a configuration that allows the condensate to be promptly discharged, which provides a high heat exchanger effectiveness.

Furthermore, a rib **84** is provided in a standing manner on the bottom wall part **31** of the casing **30** at a position closer to the vehicle body front than the flat surface portion **31a** and along the flowing direction of the air introduced through the intermediate duct **5**. The rib **84** can prevent the condensate collected at the drain port **80** from being taken into the evaporator **33** by the air flow sent to the air conditioning unit **4**. The condensate, in particular, tends to obliquely downwardly flow on the bottom surface of the evaporator **33** and then fall down, at the vehicle body front side thereof, to the bottom wall part **31**. Therefore, the condensate is most likely to fall down, at the side of the evaporator **33** closer to the vehicle body front than the rib **84**, to the bottom wall part **31**. The rate of air flow at the side of the bottom wall part **31** closer to the vehicle body front than the rib **84** is relatively low, and the interference of the air flow with dropping down and collection of condensate can be significantly reduced.

Further, an attachment part **85** for attaching the air conditioning unit **4** to the dash panel **P** is provided integrally with the exit **82** of the drain passage **81**. In attaching the air conditioning unit **4**, a stud bolt fixed to the dash panel **P** is inserted into a hole of the attachment part **85**, and then the dash panel **P** is fastened by the stud bolt and a nut. Therefore, when the drain pipe **83** is assembled with the dash panel **P**, the drain pipe **83** and the dash panel **P** are free from wobbling to enhance sealing property.

The air conditioning unit **4** is divided into two sections one on another, and the casing **30** consists of the body part **32** forming an upper casing and the side wall part **31** forming a lower casing. Further, the body part **32** is divided into right and left portions. The evaporator **33** and the heater core **34** are held sandwiched between the two divided portions of the body part **32**. This facilitates the assembly of the evaporator **33** and heater core **34** and ensures their retention. Furthermore, in order to take only the evaporator **33** out of the air conditioning unit **4** without disassembling the body part **32**, a cover as a separate member is provided on the left side wall **30a** (the air blowing unit side) of the casing **30**. The upper half of the horizontal duct **5b** or a cover **81b** for the drain passage **81** may be provided on the cover, or may be left formed together with the body part **32**.

Use of such a divided configuration of the casing eliminates the need for vertical separation of the bottom wall part **31** and therefore eliminates fear of leakage of condensate.

Next, the drain passage will be described in detail. In general, for the formation of the drain passage **81** as a hollow body integral with the bottom wall part **31**, an elongated core has to be set in molding the bottom wall part **31**. It is difficult to form a deep, narrow, elongated groove due to difficulties in precise fabrication of the core and suitable adjustment of the draft angle. Therefore, the formation of an elongated groove has a limitation.

On the contrary, in the present invention, the drain passage **81** is formed by two separate parts, i.e., an elongated groove part **81a** and a cover **81b**. The elongated groove part **81a** is formed integrally with the bottom wall part **31**, while the

cover **81b** is formed integrally with the body part **32**. This enables easy formation of the elongated groove part **81a** even if the depth and length thereof are rather large, provides flexibility to the shape and size of the drain passage **81**, ensures a space for storing condensate, and provides the configuration of the space that can drain off condensate smoothly. Furthermore, there can be increased design flexibility to the position at which the drain pipe **83** is to be attached to the dash panel **P**.

The heater core **34** is a heating heat exchanger for heating the air having passed through the evaporator **33**, and is made of tubes and fins stacked in the same manner as in the evaporator **33**. In the heater core **34**, a high-temperature cooling water from the engine circulates in the tubes to heat the air passing through the heater core **34**. The heater core **34** is provided with heater pipes **91**, one for introducing the engine cooling water and the other for discharging it. Like each cooler pipe for the evaporator **33**, each heater pipe **91** is formed to extend outwardly from the left side wall **30a** of the casing **30** and then extend toward the front of the vehicle body. Therefore, the heater pipes **91** are also disposed in the space between the air conditioning unit **4** and the air blowing unit **3**, which provides effective use of this space. Furthermore, since the heater pipes **91** are located above the intermediate duct **5**, the front passenger does not touch these pipes and therefore the attachment of heat insulators to the heater pipes can be eliminated.

This embodiment is designed so that various heater cores **34** different in height can be disposed inside of the casing **30**. This embodiment, in particular, is the type provided with a short heater core **34**. Therefore, in this embodiment, the casing has a small opening area formed in accordance with such a short heater core **34**, and the other portions of the casing are not different from the other types. If a tall heater core is used, the opening area is formed in accordance with the height of the heater core and the other portions are common to the other types. In other words, two air mixing dampers **36** and **37** and a partition **40** are not changed but are common among plural types of casings.

Between the evaporator **33** and the heater core **34**, two air mixing dampers (temperature control dampers) **36** and **37** are disposed for controlling the temperature of a conditioned air. The temperature control of the air mixing dampers **36** and **37** is made by changing the ratio of air having passed through the evaporator **33** between the flow rates of a partial air passing through the heater core **34** and another partial air passing through a bypass passage **38** for allowing part of the air having passed through the evaporator **33** to bypass the heater core **34**.

More specifically, as shown in FIG. 6, the inner space of the casing **30** in the air conditioning unit **4** is divided into an evaporator space **41** for accommodating the evaporator **33** and a heater core space **42** for accommodating the heater core **34** by a partition **40** formed integrally with the inner surface of the casing **30**. This partition **40** consists of a front partition **40a** toward the vehicle body front and a rear partition **40b** toward the vehicle body rear. In the sectional view of the air conditioning unit **4** looking in the car widthwise direction in FIG. 6, the front partition **40a** extends substantially horizontally and the rear partition **40b** has the shape of an inverted V. The front and rear partitions **40a** and **40b** have respective openings **43** and **44** for bringing the evaporator space **41** into communication with the heater core space **42**. The openings **43** and **44** are opened and closed by the air mixing dampers **36** and **37**, respectively. The rear partition **40b** has also an open-

ing **48** located at the rear of the heater core space **42**. The opening **48** communicates the bypass passage **38** with the evaporator space **41**.

Although not shown, a rib may be provided integrally on the inner surface of the casing **30** between the lower end of the air mixing damper **36** in open position and the evaporator **33**. Such a rib smoothly guides the air flow from the evaporator into the inside of the casing, and prevents the air flow from entering between the lower end of the air mixing damper **36** and the casing inner surface.

The two air mixing dampers **36** and **37** each have a shaft extending in the car widthwise direction like the inside/outside air switching damper **12**. Both ends of the shaft is supported to the casing **30**, and the left end of the shaft is coupled via a link mechanism **46** to the output shaft of an actuator **45** disposed on the left side wall **30a** of the casing **30**. The actuator **45** is fixed to a boss extended from the casing left side wall **30a**, like the actuator **15** for the inside/outside air switching damper **12**.

The two air mixing dampers **36** and **37** are cooperated with each other via the link mechanism **46**, and angularly moved by the actuator **45** from the position that fully opens the front-side and rear-side openings **43** and **44** to the position that fully closes them. In this case, when the rear-side air mixing damper **37** is angularly moved to the position that fully opens the rear-side opening **44**, it fully closes the opening **48** at the upstream end of the bypass passage **38** to pass almost all the air through the heater core **34**.

The two air mixing dampers **36** and **37** are preferably different in opening/closing timing for precise control, but may optionally have the same opening/closing timing. In this embodiment, when the air mixing damper **36** is fully opened, the other air mixing damper **37** is opened halfway. Then, the air mixing damper **37** is rotated to the full. When both the air mixing dampers **36** and **37** are closed, they are rotated in the reverse order.

The actuator **45** for the air mixing dampers **36** and **37** also has a coupler **49** (shown only in FIGS. 3 and 5) to which a signal line from the air conditioning controller is connected, like the actuator **15** for the inside/outside air switching damper **12**.

The evaporator **33** is equipped with a temperature sensor (not shown) for detecting the surface temperature of the evaporator **33**. The heater core **34** is equipped with a water temperature sensor (not shown) for detecting the temperature of the engine cooling water in the heater core **34**. Signal lines from these sensors are extended through the left side wall **30a** of the air conditioning unit **4** and are connected to the air conditioning controller.

The upper portion of the casing **30** has a plurality of vents **50, 50, . . .** formed in an inclined rear surface and defrosting vents **51, 51** formed in an approximately flat surface located at the front of the inclined rear surface. Further, the upper portion of the casing **30** also has leg vents **52** (only right one is shown in FIG. 6) formed in the left and right side walls **30a** and **30b** (as shown in FIGS. 5 and 10), respectively. The vents **50, 50** are connected with vent grilles **53, 53, . . .** disposed in the instrument panel **2** as shown in FIG. 4 through vent ducts (not shown). Conditioned airs from the vents **50** are mainly blown toward the upper halves of the passengers. On the other hand, the defrosting vents **51, 51** are connected with defrosting grilles **54, 54** disposed at the front end of the instrument panel **2** through defrosting ducts (not shown). Conditioned airs from the defrosting vents **51** are blown toward the inner surface of the front window. The right and left leg vents **52, 52** are connected to ducts **57, 56** extending downward, respectively. Both the ducts **56, 57** are open in the under surface of

21

the instrument panel **2** in the vicinities of the driver's and passenger's legs, respectively, from which conditioned air is blown toward the driver's and passenger's legs.

Out of the ducts **56** and **57** connected to the leg vents **52** and **52**, the driver's side duct **56** is provided integrally with the casing **30** to turn from the right side wall **30b** of the casing to the rear side wall thereof, has a relatively large sectional area, and therefore serves as a dual-purpose duct for both front and rear seats through which a conditioned air for rear passengers passes together with a conditioned air for front passengers. The front of a portion of the dual-purpose duct **56** corresponding to the casing right side wall **30b** is formed with openings **55**, **55** for blowing out the conditioned air toward the driver's seat as described above. The bottom of a portion of the dual-purpose duct **56** corresponding to the casing rear wall is formed with connecting parts **58**, **58** to which the upper ends of floor ducts (not shown) for guiding the conditioned air toward the rear passengers are connected.

Inside of the casing **30** of the air conditioning unit **4**, two blow-out direction switching dampers **60** and **61** are provided for opening and closing the vents **50**, **51** and **52** to change the blow-out direction of the conditioned air, in the same manner as with the air mixing dampers **36** and **37**. These dampers **60** and **61** are operated by a link mechanism **62** disposed on the left side wall **30a** of the casing **30** of the air conditioning unit **4** and an actuator **63** fixed to the boss on the left side wall **30a**.

Front-side one of the blow-out direction switching dampers **60** and **61** is a defrosting damper **60** for opening and closing the defrosting vents **51** and **51**, while rear-side one is a vent damper **61** for opening and closing the vents **50**, **50**, The dampers **60** and **61** are cooperated with each other via the link mechanism **62**, and each driven by the actuator **63** to openings corresponding to a plurality of air blowing modes. Specifically, the air conditioning unit **4** is changeable, according to the open/closed positions of the two dampers **60** and **61**, to any one of the air blowing modes including vent mode, defrosting mode, leg mode, and bi-level mode in which air is blown out through the vents **50** and the leg vents **52**. The actuator **63** for the blow-out direction switching dampers **60** and **61** also has a coupler **65** (shown in FIGS. **3** and **5**) to which a signal line from the air conditioning controller is connected, like the actuator **15** for the inside/outside air switching damper **12**.

As described above, the link mechanisms **46** and **62** and the actuators **45** and **63** for the dampers **36**, **37**, **60** and **61** in the air conditioning unit **4** are together disposed on the left side wall **30a** of the air conditioning unit **4**. Therefore, these components can be attached to the air conditioning unit **4** at a time from a single direction in assembling the air conditioning unit **4**.

Next, description will be made about the installation of the air conditioner **1** on the vehicle body. Attachment parts for the air blowing unit **3** and the air conditioning unit **4** will be first described. The air blowing part **8** of the air blowing unit **3** is provided at the right and left sides with a pair of attachment legs **68** and **68**. The filter accommodation part **21** is provided with an attachment leg **69** extending from the right side wall toward the right side of the vehicle body. On the other hand, attachment parts for the air conditioning unit **4** includes an attachment part **85** on an attachment leg **70** formed integrally with the drain **35**, and attachment parts on a pair of attachment legs **71** and **71** provided at the right and left side of the top of the casing **30**.

The attachment legs **68**, **69**, **70** and **71** of the air blowing and air conditioning units **3** and **4** are formed with through holes, respectively. The dash panel **P** is provided with stud bolts (not shown) attached to align themselves with the

22

through holes. As shown in FIG. **12**, the dash panel **P** is formed with through holes **102** corresponding to the respective positions where the cooler pipes **90**, the heater pipes **91** and the drain passage **81** are disposed. With this configuration, when the air conditioner **1** is positioned with respect to the vehicle body to insert the stud bolts into the corresponding through holes in the attachment parts **68-71** of the units **3** and **4**, the cooler pipes **90** and the heater pipes **91** are presented to the engine room through the through holes **102** in the dash panel **P**. In this state, nuts are screwed on the stud bolts thereby firmly fixing the air conditioner **1** to the vehicle body. Furthermore, the cooler pipes **90** and the heater pipes **91** are connected to corresponding pipes in the engine room, while the drain pipe **83** is connected to a final drain pipe. The connection work for all the cooler, heater and drain pipes **90**, **91** and **83** can be carried out at close hand from the engine room side, which reduces the number of processes.

Next, the sealing mechanism of the air conditioner **1** and the dash panel **P** will be described. A dash insulator **D** is attached to the passenger's room side of the dash panel **P**. Cushion sealing members **101** are attached to the outer peripheries of the cooler, heater and drain pipes **90**, **91** and **83**. In this embodiment, a single sealing member **101** is attached to the heater pipes **91** and one of the cooler pipes **90**. Another two sealing members **101** are attached individually to the other cooler pipe **90** and the drain pipe **83**.

The dash panel **P** is formed with through holes **102** for passing the corresponding pipes **90**, **91** and **83** therethrough. The dash insulator **D** is formed with openings **103** larger in diameter than the through holes **102** and smaller in diameter than the recesses in the bracket **92**. With this configuration, in assembly, the bracket **92** is pressed against the dash insulator **D** to seal the openings **103** and the sealing members **101** are pressed against the dash panel **P** to seal the through holes **102** in the dash panel **P**. Such a double sealing structure increases sealing properties.

Furthermore, in the air conditioner for an automobile according to this embodiment, an air from the air blowing unit **3** is sent to the air conditioning unit **4** through the intermediate duct **5**. The link mechanisms **46** and **62** and actuators **45** and **63** for the air mixing dampers **36** and **37** and the air blow-out direction switching dampers **60** and **61** in the air conditioning unit **4** are attached to the air blowing unit side of the air conditioning unit casing **30**. The actuator **15** for the inside/outside air switching damper **12** in the air blowing unit **3** is attached to the air conditioning unit side of the air blowing unit casing **6**. Therefore, the link mechanisms **46** and **62** and the actuators **15**, **45** and **63** can be accommodated in a dead space located above the intermediate duct **5**, thereby reducing the size of the air conditioner **1** and the installation space therefore. Furthermore, the link mechanisms **46** and **62** and the actuators **45** and **63** can be assembled with the air conditioning unit casing **30** from a single direction. This reduces the number of assembly processes for the air conditioning unit **4**.

The couplers **17**, **27**, **49** and **65**, which connect the actuators **15**, **45** and **63** for the dampers **12**, **36**, **37**, **60** and **61**, the temperature sensor for the evaporator **33**, the water temperature sensor for the heater core **34** and the control circuit **26** for the air blowing fan **23** with the air conditioning controller, are collected in the space between the air blowing unit **3** and the air conditioning unit **4**. This reduces the number of processes for assembly of the air conditioner **1** with the vehicle body.

The right side wall **30b** (the driver's side) of the air conditioning unit **4** is not provided with the link mechanisms **46** and **62** and the actuators **45** and **63**, which increases the sectional area of the driver's side duct **56** and the design flexibility to

23

the duct **56**. This increases the usefulness of the right side wall **30b** of the air conditioning unit **4**. In other words, the amount of air blow for the driver and passengers can be ensured sufficiently by the duct **56** alone. In addition, a space in the vicinity of the driver's legs can be increased.

FIGS. **19** to **23** show an air conditioner according to another embodiment of the present invention. This embodiment is directed to an air conditioner for a left-hand drive car in which the air conditioning unit **4** is placed substantially in the car widthwise middle of the instrument panel **2** and the air blowing unit **3** is placed to the front-passenger's seat side of the air conditioning unit **4** (toward the right of FIG. **19**). Description will be made about only different parts from the first embodiment, and will be omitted about the other parts.

Two heater pipes **91** are juxtaposed one above the other like the first embodiment, while two cooler pipes **90** are disposed laterally and collected by a block **100**. The vertical plane that divides the bracket **92** into the fixed and detachable brackets **92a** and **92b** runs through the vertical center lines of the heater pipes **91** and the center line of the block **100**. The seal plate **93a** is assembled into the fixed and detachable brackets **92a** and **92b** by being slidably inserted into them from below. The seal plate **93a** has recesses whose diameters correspond to the outer diameters of the two cooler pipes **90** and which surround two thirds of the pipes to simultaneously fix the two cooler pipes **90**. This increases the retention to the cooler pipes **90** when the seal plate **93a** is inserted into the brackets.

The outer diameters of the cooler and heater pipes **90** and **91** herein referred to may be actual outer diameters thereof, if fitting members such as cushion members or heat insulators are fitted onto the pipes, may be outer diameters of the fitting members or the compressed fitting members.

FIG. **24** shows an exemplary attachment structure of the expansion valve box **96**. As shown in FIG. **22**, the expansion valve box **96** is disposed in the outside wall of the body part **32** in an embedded manner. Typically, when the expansion valve box **96** is assembled with the casing **30** by connecting it to the evaporator **33**, a butyl rubber member or the like is adhered to an exposed portion of the expansion valve box **96** to cover the exposed portion, thereby preventing exposure to the outside air and condensation. In this embodiment, however, an extended wall **30a** is formed integrally with the casing **30** to surround the expansion valve box **96**. The expansion valve box **96** is first accommodated in the extended wall **30a**, the extended wall **30a** is covered with a cover **30b** in close contact, and the extended wall **30a** and the cover **30b** are fastened with a bolt. In this manner, the expansion valve box **96** can be prevented from being exposed to the outside air. At the removal of the expansion valve box **96**, the cover **30b** need only be detached. On the other hand, at the attachment of the expansion valve box **96**, it is necessary only to accommodate the expansion valve box **96** in the extended wall **30a** and then insert the cover **30b** onto the extended wall **30a** again. This provides easy attachment and detachment of the expansion valve box **96**. Further, no sealing member such as a butyl rubber is consumed for each attachment, which results in reduced cost and improved environment.

In the embodiment of FIG. **22**, two cooler pipes connected to the expansion valve box are provided to extend substantially at a right angle from each other. Two cooler pipes, however, may be extended in the same direction. In particular, two cooler pipes may be arranged toward the cover **30b** and extended in a direction in which the cover is inserted onto and pulled out of the expansion valve box. Further, the extended wall may be higher than the height of the expansion valve to cover the expansion valve. Alternatively, the extended wall

24

may be lower than the height of the expansion valve and the cover may have a flange for covering the periphery of the expansion valve.

Furthermore, in the above embodiments, the intermediate duct **5** has an inclined duct **5a** as a separate member and a horizontal duct **5b** formed integrally with the casing **30**. However, the inclined and horizontal ducts **5a** and **5b** may be integrally formed to separate them from the casing **30**.

The above embodiments are directed to air conditioning units of the type that the evaporator is inclined in a car lengthwise direction. However, the present invention is applicable, depending upon components to be provided, to the type that the evaporator is inclined in a car widthwise direction.

INDUSTRIAL APPLICABILITY

As can be seen from the above, vehicle air conditioners of the present invention is suitable for downsizing.

What is claimed is:

1. A vehicular air conditioner comprising:

an air conditioning unit disposed substantially in an inside middle portion of an instrument panel in a widthwise direction of a vehicle body, also including a dash panel, said air conditioning unit including a casing;

an air blowing unit disposed to a front-passenger's side of the air conditioning unit;

an intermediate duct for ducting an air from the air blowing unit to the air conditioning unit;

a cooling heat exchanger and a heating heat exchanger disposed in the air conditioning unit; cooler pipes connected to the cooling heat exchanger and heater pipes connected to the heating heat exchanger are arranged to extend from the same side of the air conditioning unit in the widthwise direction of the vehicle;

a space provided under the cooling heat exchanger in the casing into which air from the intermediate duct is introduced;

a drain part having a drain passage integrally formed with a bottom wall part of the casing and projecting out from a side wall part of the air conditioning unit on the air blowing unit side, with a downstream portion of the drain part extending toward the front of the vehicle body and an exit of the drain part being located closer to the front of the vehicle body than the intermediate duct; wherein the exit of the drain part is connected with a drain pipe extending toward a front portion of the vehicle body;

a through hole formed in the dash panel of the vehicle body, wherein said drain pipe is inserted into said through hole; and

wherein said air conditioner allows the air introduced from the intermediate duct into the air conditioning unit to pass through the cooling and heating heat exchangers disposed in the air conditioning unit to produce a conditioned air,

said cooling heat exchanger is inclined downwardly toward a front portion of the vehicle body,

said intermediate duct is provided between said blowing unit and said air conditioning unit and is connected to a lower side of said cooling heat exchanger, and said drain part is provided below said cooling exchanger.

2. The vehicular air conditioner as defined in claim 1, wherein the air conditioning unit includes an attachment part for attachment to the vehicle body, said attachment part being integrally formed with said drain part.

25

3. The vehicular air conditioner as defined in claim 1, wherein the drain pipe extends in a direction orthogonal to the dash panel.

4. The vehicular air conditioner as defined in claim 1, wherein the casing of the air conditioning unit is divided into an upper and a lower part, said lower part being a bottom wall part placed under the cooling heat exchanger and the upper part being a body part above the bottom wall part;

said body part being divided into a driver seat side member and a passenger seat side member; and
a heater pipe is supported by the passenger seat side member.

5. The vehicular air conditioner as defined in claim 1, wherein the casing of the air conditioning unit is divided into an upper and a lower part, said lower part being a bottom wall part placed under the cooling heat exchanger and the upper part being a body part above the bottom wall part;

said body part being divided into a driver seat side member and a passenger seat side member; and

the drain part is composed of an elongated groove part formed at the bottom wall part so as to be open upward and a cover is integrally formed with the body part covering the elongated groove part.

6. The vehicular air conditioner as defined in claim 1, wherein the drain part is positioned at the lowest level in the

26

bottom wall part of the casing of the air conditioning unit, and a portion, opposite to the drain part and on the driver seat side, is positioned at the highest level; and

said bottom wall part has an inclined surface inclining downward from said portion on the driver seat side toward the drain part.

7. The vehicular air conditioner as defined in claim 6, wherein said intermediate duct has an inclined part inclining downward from the air blowing unit toward the air conditioning unit and a direction switching part connecting the inclined part and the air conditioning unit; and

a bottom face of the direction switching part is substantially horizontal.

8. The vehicular air conditioner as defined in claim 7, wherein a cooler pipe and a heater pipe project out from a side wall part of the air conditioning unit on the air blowing unit side and bend to extend toward the front of the vehicle.

9. The vehicular air conditioner as defined in claim 1, wherein a side wall part of the casing of the air conditioning unit on the air blowing unit side has an opening to which the intermediate duct is connected; and

the shape of the opening is substantially a triangle with two sides getting narrower towards the front of a vehicle.

* * * * *